




EAN code  
 ZTR-8-8V: 8595188136808  
 ZTR-8-12V: 8595188136815  
 ZTR-15-12V: 8595188139281

Technical parameters	ZTR-8-8	ZTR-8-12	ZTR-15-12
<b>Entry (U prim)</b>			
Voltage range:	AC 230 V / 50 Hz		
Supply voltage tolerance:	± 10 %		
Consumption without load (max):	70 %		
<b>Output (Usec)</b>			
Output voltage:	AC 8 V	AC 12 V	AC 4 V AC 8 V AC 12 V
Output voltage-no load AC:	12 V	16 V	16 V
Max. loadability:	8 A	8 VA	4V 5VA, 8V 10 VA, 12 V 15VA
Fuse:	short-circ.resistant		
<b>Other information</b>			
Operating temperature:	-20.. +40°C (-4 °F to 104 °F)		
Storing temperature:	-20.. +60°C (-4 °F to 140 °F)		
Electrical strenght (prim/sec):	4 kV		
Protection degree:	IP20 / 40		
Max. cable size (mm <sup>2</sup> ):	solid wire max. 1x 2.5 or 2x 1.5 / with sleeve max. 1x 1.5 (AWG 12)		
Dimensions:	90 x 35.6 x 64 mm (3.5" x 1.4" x 2.6")	90 x 52 x 65 mm (3.5" x 2" x 2.6")	
Weight:	337 g (11.9 oz.)	345 g (12.2 oz.)	624 g (22 oz.)


- Designated for general use – e.g. for home bells supply, door locks supply.
  - Input voltage: AC 230 V.
  - Universal power supply with AC input voltage.
  - Short-circuit-proof, doubled output terminals.
- 2-MODULE, DIN rail mounting.  
 ZTR-8-8: output voltage 8 V.  
 ZTR-8-12: output voltage 12 V.
  - 3-MODULE, DIN rail mounting.  
 ZTR-15-12: output voltage 4, 8,12V.

#### Connection

ZTR-8-8



ZTR-8-12



ZTR-15-12

